

### Applications

- Pressure monitoring and control of processes
- Safety-critical applications in general process instrumentation, especially in the chemical and petrochemical industries, oil and gas industries, power generation incl. nuclear power plants, water/wastewater industries, mining
- For gaseous and liquid, aggressive, highly viscous or contaminated media, also in aggressive ambience
- For measuring points with limited space, e.g. control panels

### Special features

- No power supply needed for switching of electrical loads
- Robust switch enclosure from aluminium alloy or stainless steel, IP66, NEMA 4X
- Setting ranges from 0.2 ... 1.2 bar to 200 ... 1,000 bar, vacuum ranges
- Repeatability of the set point  $\leq 1\%$  of span
- 1 set point, SPDT or DPDT, high switching power up to AC 250 V, 15 A



### Order numbers

Switch enclosure		Aluminium, copper-free, painted with polyurethane	
Process connection		1/4 NPT-F	
Electrical connection		1/2 NPT-F	
Contacts		A - 1 x SPDT, silver contact	B - 1 x SPDT, silver contact, hermetically sealed with argon gas
Setting range	Measuring element		
-1 ... -0.2 bar	V	14151344	14151350
0.1 ... 2.5 bar	M	14151721	14151724
0.2 ... 1.2 bar	T	14151725	14151726
0.5 ... 2.5 bar	M	14151737	14151738
0.8 ... 6 bar	M	14151740	14151742
1.6 ... 10 bar	M	14151748	14151752
4 ... 25 bar	M	14151755	14151756
8 ... 40 bar	P	14151759	14151761
16 ... 100 bar	P	14151763	14151765
40 ... 250 bar	P	14151766	14151767
80 ... 400 bar	P	14151768	14151769

Legend: available from stock in Germany available after production -- not available

Quick order code (for further details see data sheet PV 33.31)

Field no.	Code	Version				
<b>Switch enclosure</b>						
①	2	Aluminium, copper-free, painted with polyurethane				
	4	Stainless steel 316L				
<b>Measuring elements and wetted parts</b>						
②	V	Diaphragm NBR				
	T	Diaphragm PTFE				
	M	Diaphragm Inconel + O-ring FPM				
	P	Piston stainless steel 316, O-ring FPM				
	G	Diaphragm Hastelloy C276				
<b>Contacts</b>						
③	A	1 x SPDT, silver contact				
	B	1 x SPDT, silver contact, hermetically sealed with argon gas				
	C	1 x SPDT, gold-plated contact, hermetically sealed with argon gas				
	G	1 x DPDT, silver contact				
	H	1 x DPDT, silver contact, hermetically sealed with air				
<b>Setting range (in bar)</b>						
④	BAA	-1 ... -0.2 bar	V	BAG	10 ... 40 bar	M
	BAN	0.1 ... 2.5 bar	M	BAJ	16 ... 100 bar	P, G
	BAB	0.2 ... 1.2 bar	T	BAH	20 ... 100 bar	M
	BAC	0.5 ... 2.5 bar	M	BAQ	20 ... 220 bar	P, G
	BAD	0.8 ... 6 bar	M	BAK	40 ... 250 bar	P, G
	BAE	1.6 ... 10 bar	M	BAR	60 ... 250 bar	P, G
	BAO	3 ... 25 bar	P, G	BAL	80 ... 400 bar	P, G
	BAP	3.5 ... 70 bar	P, G	BAM	100 ... 600 bar	P, G
	BAF	4 ... 25 bar	M	BAS	100 ... 700 bar	P
	BAI	8 ... 40 bar	P, G	BAT	200 ... 1,000 bar	P
	<b>Process connection</b>					
	⑤	1	1/4 NPT-F			
		2	Adapter 1/2 NPT-M			
		3	Adapter 1/2 NPT-F			
<b>Electrical connection</b>						
⑥	A	1/2 NPT-F				
	I	Adapter M20 x 1.5-F				
<b>Special design features</b>						
⑦	O	Cleaning for oxygen service				
	D	Wetted parts dried				
	N	NACE				
	Z	Without				
<b>Ambient / application condition</b>						
⑧	D1	Suitable for ambient temperature to -60 °C				
	O1	Offshore				
	ZZ	Without				

Please specify approvals and certificates via free text.  
 C5 Flameproof enclosure Ex d IECEx-ATEX  
 C4 SIL 2 for functional safety

Order code: PCA     B-   S   ZZ

© 2015 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.  
 The specifications given in this document represent the state of engineering at the time of publishing.  
 We reserve the right to make modifications to the specifications and materials.