



QUICK CONNECT PNEUMATIC FITTINGS




Model	A	B	Model	A	B
A-3025-0	1.33 [33.8]	0.45 [11.5]	A-3029-0	1.33 [33.8]	0.45 [11.5]
A-3025-1	1.38 [35]	0.55 [14]	A-3029-1	1.38 [35]	0.55 [14]
A-3025-2	1.53 [38.9]	0.57 [14.6]	A-3029-2	1.53 [38.9]	0.57 [14.6]
A-3025-3	1.62 [41.1]	0.69 [17.6]	A-3029-3	1.62 [41.1]	0.69 [17.6]

A-3025 Fittings: Quick Coupling Straight
A-3029 Fittings: Quick Coupling Straight Adapter




Model	A	B
A-3026-0	0.93 [23.7]	0.93 [23.7]
A-3026-1	1.09 [27.8]	1.09 [27.8]
A-3026-2	1.20 [30.6]	1.20 [30.6]
A-3026-3	1.33 [33.8]	1.33 [33.8]

A-3026 Fittings: Quick Coupling 90 Degree



Model	A	B	Model	A	B
A-3027-0	1.49 [37.8]	0.97 [23.7]	A-3030-0	1.49 [37.8]	0.97 [23.7]
A-3027-1	1.64 [41.6]	1.09 [27.8]	A-3030-1	1.64 [41.6]	1.09 [27.8]
A-3027-2	1.83 [46.6]	1.20 [30.6]	A-3030-2	1.83 [46.6]	1.20 [30.6]
A-3027-3	1.98 [50.4]	1.33 [33.8]	A-3030-3	1.98 [50.4]	1.33 [33.8]

A-3027 Fittings: 3 Way Quick Coupling
A-3030 Fittings: 3 Way Quick Coupling Adapter



Model	A	B
A-3028-0	1.49 [37.8]	1.49 [37.8]
A-3028-1	1.64 [41.6]	1.64 [41.6]
A-3028-2	1.83 [46.6]	1.83 [46.6]
A-3028-3	1.98 [50.4]	1.98 [50.4]

A-3028 Fittings: 4 Way Quick Coupling


MODEL CHART	
Model	Coupling (O.D.) x Coupling (O.D.)
A-3025-0	3/16" x 3/16"
A-3025-1	1/4" x 1/4"
A-3025-2	5/16" x 5/16"
A-3025-3	3/8" x 3/8"
A-3026-0	3/16" x 3/16"
A-3026-1	1/4" x 1/4"
A-3026-2	5/16" x 5/16"
A-3026-3	3/8" x 3/8"
A-3029-0	1/4" x 3/16"
A-3029-1	5/16" x 1/4"
A-3029-2	3/8" x 1/4"
A-3029-3	3/8" x 5/16"

MODEL CHART	
Model	Coupling (O.D.)
A-3027-0	3/16"
A-3027-1	1/4"
A-3027-2	5/16"
A-3027-3	3/8"
A-3028-0	3/16"
A-3028-1	1/4"
A-3028-2	5/16"
A-3028-3	3/8"
A-3030-0*	1/4" x 1/4" x 3/16"
A-3030-1*	5/16" x 5/16" x 1/4"
A-3030-2*	3/8" x 3/8" x 1/4"
A-3030-3*	3/8" x 3/8" x 5/16"

*Please contact factory for metric sizes.


SPECIFICATIONS
Service: Air (no other gases or liquids).
Pressure Limits: -29.5 in Hg (-750 mm Hg) to 150 psi (10.3 bar).
Temperature Limits: 32 to 140°F (0 to 60°C).
Wetted Materials: Polyurethane, polyethylene and nylon.
Weight: 0.4 oz (11 g) to 0.7 oz (19 g).

QUICK CONNECT PNEUMATIC FITTINGS




Model	A
A-3021-1	0.79 [20.3]
A-3021-2	0.86 [21.8]
A-3021-3	0.82 [20.9]
A-3021-4	0.88 [22.4]
A-3021-5	1.01 [25.7]
A-3021-6	0.95 [24.2]

A-3021 Fittings: Quick Coupling to NPT Straight




Model	A	B
A-3022-1	0.98 [24.9]	1.26 [32]
A-3022-2	1.02 [25.9]	1.30 [33]
A-3022-3	1.09 [27.7]	1.41 [35.8]
A-3022-4	1.13 [28.8]	1.45 [36.8]
A-3022-5	1.23 [31.3]	1.53 [38.9]
A-3022-6	1.26 [32]	1.57 [39.9]

A-3022 Fittings: Quick Coupling to NPT 90 Degree



Model	A	B
A-3023-1	1.31 [33.3]	1.49 [37.8]
A-3023-2	1.35 [34.3]	1.49 [37.8]
A-3023-3	1.43 [36.3]	1.64 [41.6]
A-3023-4	1.47 [37.3]	1.64 [41.6]
A-3023-5	1.53 [38.9]	1.83 [46.6]
A-3023-6	1.57 [39.9]	1.83 [46.6]

A-3023 Fittings: 3 Way-Quick Coupling by Quick Coupling to NPT



Model	A	B
A-3024-1	1.83 [46.4]	1.02 [25.9]
A-3024-2	1.87 [47.4]	1.06 [26.9]
A-3024-3	1.97 [50.1]	1.09 [27.8]
A-3024-4	2.01 [51.1]	1.13 [28.8]
A-3024-5	2.16 [54.9]	1.23 [31.3]
A-3024-6	2.20 [55.9]	1.26 [32]

A-3024 Fittings: 3 Way-Quick Coupling by NPT to Quick Coupling

MODEL CHART	
Model	Coupling (O.D.) x NPT
A-3021-1	1/4" x 1/8"
A-3021-2	1/4" x 1/4"
A-3021-3	5/16" x 1/8"
A-3021-4	5/16" x 1/4"
A-3021-5	3/8" x 1/8"
A-3021-6	3/8" x 1/4"
A-3022-1*	1/4" x 1/8"
A-3022-2*	1/4" x 1/4"
A-3022-3*	5/16" x 1/8"
A-3022-4*	5/16" x 1/4"
A-3022-5*	3/8" x 1/8"
A-3022-6*	3/8" x 1/4"

*Please contact factory for metric sizes.

MODEL CHART	
Model	Coupling (O.D.) x NPT x Coupling (O.D.)
A-3023-1	1/4" x 1/4" x 1/8"
A-3023-2	1/4" x 1/4" x 1/4"
A-3023-3	5/16" x 5/16" x 1/8"
A-3023-4	5/16" x 5/16" x 1/4"
A-3023-5	3/8" x 3/8" x 1/8"
A-3023-6	3/8" x 3/8" x 1/4"
A-3024-1*	1/4" x 1/4" x 1/8"
A-3024-2*	1/4" x 1/4" x 1/4"
A-3024-3*	5/16" x 5/16" x 1/8"
A-3024-4*	5/16" x 5/16" x 1/4"
A-3024-5*	3/8" x 3/8" x 1/8"
A-3024-6*	3/8" x 3/8" x 1/4"

*Please contact factory for metric sizes.

SPECIFICATIONS
Service: Air (no other gases or liquids).
Wetted Materials: Polyurethane, polyethylene and nylon. Note: (A-3021 nickel plated brass).
Pressure Limits: -29.5 in Hg (-750 mm Hg) to 150 psi (10.3 bar).
Temperature Limits: 32 to 140°F (0 to 60°C).
Weight: 0.4 oz (11 g) to 0.7 oz (19 g).